

3M™ NFRC Certified Whole Window Specifications for Window Film –

3M Film Type	Film/Glass combo	SHGC	VLT	Luminous Efficacy
Amber 35	Residentail Single Clear	0.20	0.25	1.3
	Commercial Single Clear	0.24	0.27	1.1
Amber 35 LE	Residentail Single Clear	0.20	0.25	1.3
	Commercial Single Clear	0.23	0.27	1.2
Ceramic 30	Residentail Single Clear	0.35	0.30	0.9
	Commercial Single Clear	0.38	0.32	0.8
Ceramic 40	Residentail Single Clear	0.4	0.37	0.9
	Commercial Single Clear	0.44	0.40	0.9
Ceramic 50	Residentail Single Clear	0.46	0.44	1.0
	Commercial Single Clear	0.49	0.48	1.0
Neutral 20	Residentail Single Clear	0.27	0.13	0.5
	Commercial Single Clear	0.31	0.14	0.5
Neutral 35	Residentail Single Clear	0.38	0.30	0.8
	Commercial Single Clear	0.41	0.32	0.8
Neutral 50	Residentail Single Clear	0.49	0.43	0.9
	Commercial Single Clear	0.52	0.47	0.9
Neutral 70	Residentail Single Clear	0.60	0.58	1.0
	Commercial Single Clear	0.63	0.62	1.0
Nickel 50	Residentail Single Clear	0.37	0.42	1.1
	Commercial Single Clear	0.41	0.45	1.1
Night Vision 15	Residentail Single Clear	0.23	0.12	0.5
	Commercial Single Clear	0.27	0.13	0.5
Night Vision 25	Residentail Single Clear	0.33	0.20	0.6
	Commercial Single Clear	0.37	0.22	0.6
Night Vision 35	Residentail Single Clear	0.40	0.29	0.7
	Commercial Single Clear	0.44	0.30	0.7
Prestige 40	Residentail Single Clear	0.34	0.33	1.0
	Commercial Single Clear	0.38	0.36	0.9
Prestige 40 Exterior	Residentail Single Clear	0.35	0.35	1.0
	Commercial Single Clear	0.36	0.37	1.0
Prestige 50	Residentail Single Clear	0.37	0.42	1.1
	Commercial Single Clear	0.41	0.45	1.1
Prestige 60	Residentail Single Clear	0.40	0.50	1.3
	Commercial Single Clear	0.44	0.55	1.3
Prestige 70	Residentail Single Clear	0.42	0.58	1.4
	Commercial Single Clear	0.47	0.63	1.3
Prestige 70 Exterior	Residentail Single Clear	0.43	0.59	1.4
	Commercial Single Clear	0.44	0.62	1.4
Prestige 90 Exterior	Residentail Single Clear	0.57	0.73	1.3
	Commercial Single Clear	0.59	0.77	1.3
Silver 35	Residentail Single Clear	0.31	0.29	0.9
	Commercial Single Clear	0.34	0.32	0.9
Silver P18	Residentail Single Clear	0.18	0.14	0.8
	Commercial Single Clear	0.22	0.15	0.7



Renewable Energy Division
 St. Paul, MN 55144-1000
 1-800-698-4595
www.3M.com/windowfilm

3M is a trademark of 3M.
 © 3M 2008. All rights reserved.
 04/08 DMR #

3M™ Window Film

NFRC Certified Specifications

Please Note- NFRC certified specifications are slightly different than 3M printed specifications due to the fact that 3M publishes center of glass specifications, and NFRC publishes whole window specifications. For a detailed understanding of the difference between the two methods, consult 3M's technical bulletin on the difference between whole window specifications and center of glass specifications. **In order to obtain NFRC specifications, 3M's center of glass specifications are utilized in a specific window type.

Additionally NFRC specifications should be utilized for utility rebate compliance for the following reasons:

- 1) Building codes such as IECC 2009, CA Title 24, LEED, all utilize whole window specifications
- 2) The Federal HomeStar bill included window films, and recommended utilizing NFRC specifications as the mechanism for determining a rebate
- 3) US DOE Recommended energy analysis software utilize whole window specifications (eQuest, Energy Plus, Trace 700, DOE-2, and the CA SPC program as well)
- 4) These specifications are certified by a 3rd party
- 5) The NFRC requires window film manufacturers to measure the performance of their films on a specific window type. There is no other way to compare one window film manufacturer's published specification to another's, as a manufacturer may choose to publish the performance of their film on any glass type, thereby changing the performance of the film.



Renewable Energy Division

St. Paul, MN 55144-1000

1-800-698-4595

www.3M.com/windowfilm

3M is a trademark of 3M.
© 3M 2008. All rights reserved.
04/08 DMR #



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-007
Film Location:	Interior
Film Tint:	Silver
Film MFR Series:	Ultra Silver S20 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.19	0.74	0.13	1.07100
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.27	0.67	0.12	0.69800
Window Wall	6 mm (1/4in.) clear	0.75	0.22	0.80	0.14	1.01500
Window Wall	6 mm (1/4in.) grey	0.53	0.27	0.40	0.07	1.01500
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.31	0.71	0.13	0.58300
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.25	0.36	0.07	0.58300

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-013
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	Ultra PR-S50 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.37	0.74	0.41	1.09900
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.45	0.67	0.38	0.70800
Window Wall	6 mm (1/4in.) clear	0.75	0.41	0.80	0.45	1.04300
Window Wall	6 mm (1/4in.) grey	0.53	0.36	0.40	0.23	1.04300
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.48	0.71	0.40	0.59100
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.35	0.36	0.20	0.59100

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-001
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Ultra Neutral S50 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.48	0.74	0.42	1.107000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.53	0.67	0.39	0.711000
Window Wall	6 mm (1/4in.) clear	0.75	0.52	0.80	0.46	1.052000
Window Wall	6 mm (1/4in.) grey	0.53	0.42	0.40	0.23	1.052000
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.54	0.71	0.41	0.594000
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.38	0.36	0.21	0.594000

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-002
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Ultra Neutral S35 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.38	0.74	0.29	1.07400
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.46	0.67	0.27	0.70000
Window Wall	6 mm (1/4in.) clear	0.75	0.41	0.80	0.32	1.01800
Window Wall	6 mm (1/4in.) grey	0.53	0.36	0.40	0.16	1.01800
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.47	0.71	0.29	0.58400
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.34	0.36	0.14	0.58400

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-009
Film Location:	Interior
Film Tint:	Silver
Film MFR Series:	Silver P-18 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.18	0.74	0.14	1.03000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.26	0.67	0.13	0.68300
Window Wall	6 mm (1/4in.) clear	0.75	0.22	0.80	0.15	0.97300
Window Wall	6 mm (1/4in.) grey	0.53	0.26	0.40	0.07	0.97300
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.30	0.71	0.14	0.57000
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.25	0.36	0.07	0.57000

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-008
Film Location:	Interior
Film Tint:	Silver
Film MFR Series:	Silver 35 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.31	0.74	0.29	1.02100
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.37	0.67	0.27	0.68000
Window Wall	6 mm (1/4in.) clear	0.75	0.34	0.80	0.32	0.96500
Window Wall	6 mm (1/4in.) grey	0.53	0.31	0.40	0.16	0.96500
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.40	0.71	0.29	0.56800
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.30	0.36	0.15	0.56800

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-027
Film Location:	Exterior
Film Tint:	Clear
Film MFR Series:	Exterior Prestige 90

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film
Fixed	3 mm (1/8in.) clear	0.72	0.57	0.74	0.73
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.64	0.52	0.67	0.67
Window Wall	6 mm (1/4in.) clear	0.73	0.59	0.78	0.77
Window Wall	6 mm (1/4in.) grey	0.52	0.43	0.39	0.39
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.63	0.52	0.69	0.69
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.41	0.35	0.35	0.35

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-014
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	PR-70 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.42	0.74	0.58	1.079000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.47	0.67	0.52	0.701000
Window Wall	6 mm (1/4in.) clear	0.75	0.47	0.80	0.63	1.023000
Window Wall	6 mm (1/4in.) grey	0.53	0.39	0.40	0.32	1.023000
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.51	0.71	0.56	0.585000
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.36	0.36	0.28	0.585000

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-026
Film Location:	Exterior
Film Tint:	Clear
Film MFR Series:	Exterior Prestige 70

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film
Fixed	3 mm (1/8in.) clear	0.72	0.43	0.74	0.59
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.64	0.36	0.67	0.54
Window Wall	6 mm (1/4in.) clear	0.73	0.44	0.78	0.62
Window Wall	6 mm (1/4in.) grey	0.52	0.34	0.39	0.31
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.63	0.36	0.69	0.56
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.41	0.25	0.35	0.28

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-015
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	PR-60 Interior Film Attachement

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.40	0.74	0.50	1.07900
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.47	0.67	0.46	0.70100
Window Wall	6 mm (1/4in.) clear	0.75	0.44	0.80	0.55	1.02300
Window Wall	6 mm (1/4in.) grey	0.53	0.37	0.40	0.28	1.02300
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.50	0.71	0.49	0.58500
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.35	0.36	0.25	0.58600

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-016
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	PR-50 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.37	0.74	0.42	1.07900
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.45	0.67	0.38	0.70100
Window Wall	6 mm (1/4in.) clear	0.75	0.41	0.80	0.45	1.02300
Window Wall	6 mm (1/4in.) grey	0.53	0.36	0.40	0.23	1.02300
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.48	0.71	0.40	0.58500
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.35	0.36	0.20	0.58500

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-017
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	PR-40 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.34	0.74	0.33	1.07900
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.44	0.67	0.30	0.70100
Window Wall	6 mm (1/4in.) clear	0.75	0.38	0.80	0.36	1.02300
Window Wall	6 mm (1/4in.) grey	0.53	0.34	0.40	0.18	1.02300
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.47	0.71	0.32	0.58500
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.34	0.36	0.16	0.58500

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-025
Film Location:	Exterior
Film Tint:	Clear
Film MFR Series:	Exterior Prestige 40

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film
Fixed	3 mm (1/8in.) clear	0.72	0.35	0.74	0.35
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.64	0.28	0.67	0.32
Window Wall	6 mm (1/4in.) clear	0.73	0.36	0.78	0.37
Window Wall	6 mm (1/4in.) grey	0.52	0.30	0.39	0.19
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.63	0.28	0.69	0.33
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.41	0.21	0.35	0.17

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-019
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	NV-35 Interior Film Attachement

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.42	0.74	0.30	1.11000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.49	0.67	0.27	0.71200
Window Wall	6 mm (1/4in.) clear	0.75	0.45	0.80	0.32	1.05400
Window Wall	6 mm (1/4in.) grey	0.53	0.38	0.40	0.16	1.05400
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.51	0.71	0.29	0.59400
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.36	0.36	0.15	0.59400

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-020
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	NV-25 Interior Film Attachement

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.33	0.74	0.20	1.08600
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.43	0.67	0.19	0.70300
Window Wall	6 mm (1/4in.) clear	0.75	0.37	0.80	0.22	1.03000
Window Wall	6 mm (1/4in.) grey	0.53	0.34	0.40	0.11	1.03000
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.45	0.71	0.20	0.58700
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.33	0.36	0.10	0.58700

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-021
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	NV-15 Interior Film Attachement

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.23	0.74	0.12	1.06900
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.33	0.67	0.12	0.69800
Window Wall	6 mm (1/4in.) clear	0.75	0.27	0.80	0.13	1.01300
Window Wall	6 mm (1/4in.) grey	0.53	0.29	0.40	0.07	1.01300
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.36	0.71	0.12	0.58200
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.28	0.36	0.06	0.58200

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-006
Film Location:	Interior
Film Tint:	Silver
Film MFR Series:	Nickel 50 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.37	0.74	0.42	1.02100
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.41	0.67	0.38	0.68000
Window Wall	6 mm (1/4in.) clear	0.75	0.41	0.80	0.45	0.96500
Window Wall	6 mm (1/4in.) grey	0.53	0.35	0.40	0.23	0.96500
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.44	0.71	0.41	0.56800
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.32	0.36	0.21	0.56800

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-003
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Neutral 70 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.60	0.74	0.58	1.109000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.59	0.67	0.53	0.712000
Window Wall	6 mm (1/4in.) clear	0.75	0.63	0.80	0.62	1.054000
Window Wall	6 mm (1/4in.) grey	0.53	0.48	0.40	0.32	1.054000
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.60	0.71	0.56	0.594000
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.41	0.36	0.28	0.954000

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-004
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Neutral 50 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.49	0.74	0.43	0.109000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.53	0.67	0.39	0.712000
Window Wall	6 mm (1/4in.) clear	0.75	0.52	0.80	0.47	1.054000
Window Wall	6 mm (1/4in.) grey	0.53	0.42	0.40	0.24	1.054000
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.54	0.71	0.42	0.594000
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.38	0.36	0.21	0.594000

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-005
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Neutral 35 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.38	0.74	0.30	1.07600
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.46	0.67	0.27	0.70000
Window Wall	6 mm (1/4in.) clear	0.75	0.41	0.80	0.32	1.02000
Window Wall	6 mm (1/4in.) grey	0.53	0.36	0.40	0.16	1.02100
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.47	0.71	0.29	0.58500
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.34	0.36	0.15	0.58500

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-018
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Neutral 20 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.27	0.74	0.13	1.08000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.41	0.67	0.12	0.70200
Window Wall	6 mm (1/4in.) clear	0.75	0.31	0.80	0.14	1.02500
Window Wall	6 mm (1/4in.) grey	0.53	0.30	0.40	0.07	1.02500
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.42	0.71	0.13	0.58600
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.31	0.36	0.06	0.58600

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-024
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	Ceramic 50 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.46	0.74	0.44	1.115000
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.51	0.67	0.40	0.714000
Window Wall	6 mm (1/4in.) clear	0.75	0.49	0.80	0.48	1.061000
Window Wall	6 mm (1/4in.) grey	0.53	0.41	0.40	0.24	1.061000
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.53	0.71	0.43	0.596000
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.37	0.36	0.22	0.596000

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-023
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	Ceramic 40 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.40	0.74	0.37	1.11100
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.48	0.67	0.34	0.71200
Window Wall	6 mm (1/4in.) clear	0.75	0.44	0.80	0.40	1.05600
Window Wall	6 mm (1/4in.) grey	0.53	0.38	0.40	0.20	1.05700
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.50	0.71	0.36	0.59500
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.35	0.36	0.18	0.59500

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-022
Film Location:	Interior
Film Tint:	Clear
Film MFR Series:	Ceramic 30 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.35	0.74	0.30	1.10300
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.44	0.67	0.27	0.71000
Window Wall	6 mm (1/4in.) clear	0.75	0.38	0.80	0.32	1.04800
Window Wall	6 mm (1/4in.) grey	0.53	0.35	0.40	0.16	1.04800
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.46	0.71	0.29	0.59300
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.33	0.36	0.15	0.59300

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-012
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Amber 35 Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.20	0.74	0.25	
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.25	0.67	0.23	
Window Wall	6 mm (1/4in.) clear	0.75	0.24	0.80	0.27	
Window Wall	6 mm (1/4in.) grey	0.53	0.26	0.40	0.13	
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.30	0.71	0.25	
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.24	0.36	0.12	

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.



Film-Attachment Product Detail

GENERAL INFORMATION	
Manufacturer:	3M
CPD Number:	MMM-M-010
Film Location:	Interior
Film Tint:	Other
Film MFR Series:	Amber 35 LowE Interior Film Attachment

RATINGS INFORMATION

Operator Type	Default Glazing Reference	SHGC No Film	SHGC with Film	VT No Film	VT with Film	U-Factor
Fixed	3 mm (1/8in.) clear	0.71	0.20	0.74	0.25	
Fixed	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.63	0.25	0.67	0.24	
Window Wall	6 mm (1/4in.) clear	0.75	0.23	0.80	0.27	
Window Wall	6 mm (1/4in.) grey	0.53	0.24	0.40	0.13	
Window Wall	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.65	0.29	0.71	0.25	
Window Wall	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.42	0.23	0.36	0.13	

Click the column headers to sort the data according to the column header.

This web site is optimized for a display resolution of 1024x768, and requires Microsoft Internet Explorer 5.0 or higher.

Using older browsers, non-compatible browsers or disabling browser features such as JavaScript will reduce site functionality and overall appearance.

[Download the latest version of Microsoft Internet Explorer.](#)

DISCLAIMER OF LIABILITY:

In no event shall the NFRC be liable for any damages whatsoever (including, without limitation, damages for loss of business profits, business interruption, loss of business information, or any other loss) arising out of the use of this website or the information obtained from it, whether incidental or consequential. This provision shall apply even if the NFRC has been advised of the possibility of such damages.